

Utility - Metering and Streetlighting Products

**SLC & SLOC - Insulated Streetlight Connectors**

- \* Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- \* Insulation is clear allowing easier installation with a dielectric strength of 240v per mil
- \* Dual rated for copper or aluminum conductors
- \* Meets or exceeds ANSI C119.4 Class A specifications
- \* Range taking design reduces inventory
- \* Rated for 600 Volts



SLC1/0-3P



SLOC1/0-3P



SLCS4A-4P


Catalog Number	Number of Ports	Hex Size	Dimensions, Inches			Wire Range KCMIL
			L	W	H	
SLC4-3P	3	S	1.54	1.12	1.38	#4 - #14
SLC4-4P	4	S	1.97			
SLOC4-4P	4	S	1.97	1.24		
SLCS4-4P	4	S	1.43	1.75	1.87	
SLC1/0-3P	3	3/16"	2.27	1.62	1.75	1/0 - #14
SLOC1/0-3P	3	3/16"	2.27	1.75		
SLC3/0-3P	3	1/4"	2.65	1.75	1.87	3/0 - #14
SLOC3/0-3P	3	1/4"	2.65	1.87		

Also available in Black insulation - replace C with B from catalog number - ex. SLB4-3P

OPTIONS:

- A - Allen set screws (1/8" Hex, #4 Size)
- For omission of oxide inhibitor delete suffix "P"

Example:  
SLC4-3P



Consult factory for additional configurations not listed