

Utility - Metering and Streetlighting Products

PL & PPL - Single Hole Solderless Lugs

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Tin plated to provide very low contact resistance and inhibit corrosion
- * Dual rated for copper or aluminum conductors
- * Chamfered wire entry provides ease of installation
- * UL listed to 90C
- * Rated for 600 volts
- * Mounting holes at standard NEMA 1.75" spacing



PL250
SHOWN



PL350-2N
SHOWN



PPL600-2N
SHOWN

Catalog Number	Wire Range KCMIL/AWG	Stud Size	Dimensions, Inches			Hex Size
			W	H	L	
PL6	#6 - #14	1/4	0.50	0.50	1.06	SLOT
PL2	#2 - #14	1/4	0.50	0.55	1.16	SLOT
PL1/0	1/0 - #14	1/4	0.63	0.78	1.47	3/16
PL2/0	2/0 - #14	1/4	0.63	0.78	1.47	3/16
PL250	250 - #6	5/16	0.88	1.02	2.00	5/16
PL350	350 - #6	3/8	0.99	1.13	2.25	5/16
PL500	500 - #4	3/8	1.20	1.41	2.75	3/8
PL600	600 - #2	3/8	1.38	1.51	3.18	3/8
PL800	800 - 300	1/2	1.44	1.69	3.25	1/2
PL1000	1000 - 350	1/2	1.69	1.88	3.25	9/16
PL250-2N	250 - #6	1/2	0.88	1.02	3.88	5/16
PL350-2N	350 - #6	1/2	0.99	1.13	4.25	5/16
PL500-2N	500 - #4	1/2	1.20	1.41	4.65	3/8
PL600-2N	600 - #2	1/2	1.38	1.51	4.65	3/8
PL800-2N	800 - 300	1/2	1.44	1.69	4.75	1/2
PL1000-2N	1000 - 350	1/2	1.69	1.88	4.94	9/16
PPL250-2N	250 - #6	1/2	0.88	1.02	5.00	5/16
PPL350-2N	350 - #6	1/2	0.99	1.13	5.25	5/16
PPL500-2N	500 - #4	1/2	1.20	1.41	5.50	3/8
PPL600-2N	600 - #2	1/2	1.38	1.51	5.50	3/8
PPL800-2N	800 - 300	1/2	1.44	1.69	5.75	1/2
PPL1000-2N	1000 - 350	1/2	1.69	1.88	6.19	9/16

*Oxide inhibitor is recommended for all aluminum terminations.