



**Utility - Overhead Connectors**

**PNMRTL - Nema Mount Transformer Connector**

- \* Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- \* Predrilled 1/2" mounting holes allow for easy attachment and may be bolted back to back for heavy duty applications
- \* Dual rated for copper or aluminum conductors
- \* Meets or exceeds ANSI C119.4 Class A specifications
- \* Range taking design reduces inventory
- \* Mounting holes at standard NEMA 1.75" spacing
- \* Rated for 600 volts




PNMRTL350-4P  
SHOWN

Catalog Number	Number of Ports	Dimensions, Inches			Wire Range KCMIL
		L	W	H	
PNMRTL250-4P	4	6.63	0.88	1.13	250 - #10
PNMRTL250-6P	6	8.35			
PNMRTL250-8P	8	10.07			
PNMRTL350-4P	4	7.07	0.88	1.25	350 - #10
PNMRTL350-6P	6	9.07			
PNMRTL350-8P	8	11.07			
PNMRTL500-4P	4	7.94	1.13	1.63	500 - #10
PNMRTL500-6P	6	10.19			
PNMRTL500-8P	8	12.44			
PNMRTL750-4P	4	8.34	1.25	1.75	750 - 1/0
PNMRTL750-6P	6	10.96			
PNMRTL750-8P	8	13.58			

**OPTIONS:**

- A - Anodized set screws
- SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
- For omission of oxide inhibitor delete suffix "P"

Example:  
PNMRTL350-4SLP



Inhibitor (must be last)

Consult factory for additional configurations not listed