



Utility - Overhead Connectors

PSEC - Overhead Distribution Connector

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Range taking design reduces inventory
- * Rated for 600 Volts



PSEC14-750500
SHOWN



PSEC26-750500
SHOWN

Catalog Number	Main Wire Range KCMIL	Tap Wire Range KCMIL	Number of Main Ports	Number of Tap Ports	Dimensions, Inches		
					L	W	H
PSEC14-750500P	750-1/0	500-#10	1	4	4.00	2.50	2.50
PSEC14-750600P	750-1/0	600-#10	1	4			
PSEC24-750500P	750-1/0	500-#10	2	4	4.00	3.50	2.50
PSEC24-750600P	750-1/0	600-#10	2	4			
PSEC26-750500P	750-1/0	500-#10	2	6	4.00	3.50	2.50
PSEC26-750600P	750-1/0	600-#10	2	6			
PSEC26-1000500P	1000-500	500-#10	2	6	4.50	4.00	2.50
PSEC26-1000600P	1000-500	600-#10	2	6			
PSEC26-1000750P	1000-500	750-1/0	2	6	4.50	4.06	2.50

OPTIONS:

- A - Anodized set screws
- T - Tin plated
- C - UV resistant cover

For omission of oxide inhibitor delete suffix "P"

Example:

PSEC26-750500P

Inhibitor (must be last)

Consult factory for additional configurations not listed