

Utility - Pedestal Connectors

IPCLZ & IPLZ - Insulated "Z" Pedestal Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Insulation is clear allowing easier installation with a dielectric strength of 240v per mil
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Range taking design reduces inventory
- * Rated for 600 Volts



IPCLZ500-8P
SHOWN

Catalog Number	Number of Ports	Connector Dimensions, Inches			Wire Range KCMIL
		L	W	H	
IPCLZ350-4P	4	2.12	2.00	2.26	350 - #10
IPCLZ350-6P	6	3.12			
IPCLZ350-8P	8	4.12			
IPCLZ500-4P	4	2.37	2.38	2.88	500 - #10
IPCLZ500-6P	6	3.50			
IPCLZ500-8P	8	4.63			
IPCLZ750-4P	4	2.75	2.50	3.38	750 - 1/0
IPCLZ750-6P	6	4.06			
IPCLZ750-8P	8	5.37			

Also available in Black insulation - remove C from catalog number - ex. IPLZ350-6P

OPTIONS:

- A - Anodized set screws
- SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
- For omission of oxide inhibitor delete suffix "P"

Example:
IPCLZ500-8P

Inhibitor (must be last)



Consult factory for additional configurations not listed