



Utility - Pedestal Connectors

IPLC - Insulated Pedestal Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Insulation is clear allowing easier installation with a dielectric strength of 240v per mil
- * Also available in UV resistant Black plastisol
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Range taking design reduces inventory
- * Rated for 600 Volts
- * Mounting holes available




Catalog Number	Number of Ports	Dimensions, Inches			Wire Range KCMIL
		L	W	H	
IPLC250-3P	3	2.93	2.03	2.18	250 - #10
IPLC250-4P	4	3.80			
IPLC250-6P	6	5.22			
IPLC350-3P	3	3.52	2.26	1.96	350 - #10
IPLC350-4P	4	4.65			
IPLC350-6P	6	6.90			
IPLC500-3P	3	4.14	2.50	2.56	500 - #10
IPLC500-4P	4	5.38			
IPLC500-6P	6	7.86			
IPLC750-3P	3	4.57	3.38	3.25	750 - 1/0
IPLC750-4P	4	6.00			
IPLC750-6P	6	8.85			

OPTIONS:

- A - Anodized set screws
- B - Black plastisol (replace the IPLC with IPLB)
- D - Dual Entry (IPLCD or IPLBD Prefix)
- 2M - Mounting holes
- For omission of oxide inhibitor delete suffix "P"

Example:
IPLC350-6P



Consult factory for additional configurations not listed