



Utility - Pedestal Connectors

PL - Pedestal Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Range taking design reduces inventory
- * Rated for 600 Volts
- * Mounting holes available




PL350-4CP
SHOWN

Catalog Number	Number of Ports	Dimensions, Inches			Wire Range KCMIL
		L	W	H	
PL250-3P	3	2.68	0.88	1.13	250-#10
PL250-4P	4	3.55			
PL250-6P	6	5.27			
PL250-8P	8	6.99			
PL350-3P	3	3.02	0.88	1.25	350-#10
PL350-4P	4	4.02			
PL350-6P	6	6.02			
PL350-8P	8	8.02			
PL500-3P	3	3.67	1.13	1.63	500-#10
PL500-4P	4	4.80			
PL500-6P	6	7.05			
PL500-8P	8	9.30			
PL750-3P	3	4.29	1.25	1.75	750-1/0
PL750-4P	4	5.71			
PL750-6P	6	8.56			
PL750-8P	8	11.41			

OPTIONS:

- A - Anodized set screws
 - SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
 - C - Connector with Black cover
 - T - Tin plated
 - 2M - Mounting holes
- For omission of oxide inhibitor delete suffix "P"

Example:
PL350-4CP



Consult factory for additional configurations not listed