



Utility - Pedestal Connectors

**PLZ - "Z" Pedestal Connectors**

- \* Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- \* Dual rated for copper or aluminum conductors
- \* Meets or exceeds ANSI C119.4 Class A specifications
- \* Range taking design reduces inventory
- \* Rated for 600 Volts




PLZ500-8P  
SHOWN

Catalog Number	Number of Ports	Dimensions, Inches			Wire Range KCMIL
		L	W	H	
PLZ350-4P	4	2.12	2.00	2.26	350 - #10
PLZ350-6P	6	3.12			
PLZ350-8P	8	4.12			
PLZ500-4P	4	2.37	2.38	2.88	500 - #10
PLZ500-6P	6	3.50			
PLZ500-8P	8	4.63			
PLZ750-4P	4	2.75	2.50	3.38	750 - 1/0
PLZ750-6P	6	4.06			
PLZ750-8P	8	5.37			

OPTIONS:

- A - Anodized set screws
- T - Tin plated
- SL - 1/0 - #14 Streetlight Outlet, adds apx. 7/8" to length
- For omission of oxide inhibitor delete suffix "P"

Example:  
PLZ500-8P



Consult factory for additional configurations not listed