



Utility - Single Phase Transformer Connectors for Underground Use

IPCTLZ - Insulated "Z" Transformer Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Insulation is clear allowing easier installation with a dielectric strength of 240v per mil
- * Dual rated for copper or aluminum conductors
- * Meets or exceeds ANSI C119.4 Class A specifications
- * Range taking design reduces inventory
- * Rated for 600 Volts




IPCTLZ500-61SLP
SHOWN

Catalog Number		Stud Size	Number of Ports	Connector Dimensions, Inches			Wire Range KCMIL
Slip Fit	Screw-on			L	W	H	
IPCTLZ350-658P	IPCTLZ350-658SP	5/8"-11	6	4.25	1.75	2.23	350 - #10
IPCTLZ350-858P	IPCTLZ350-858SP	5/8"-11	8	5.25			
IPCTLZ350-61P	IPCTLZ350-61SP	1"-14	6	4.31	2.25	2.88	
IPCTLZ350-81P	IPCTLZ350-81SP	1"-14	8	5.31			
IPCTLZ500-61P	IPCTLZ500-61SP	1"-14	6	5.10	2.25	2.88	500 - #10
IPCTLZ500-81P	IPCTLZ500-81SP	1"-14	8	6.23			
IPCTLZ600-61P	IPCTLZ600-61SP	1"-14	6	5.13	2.25	2.88	600 - #6
IPCTLZ600-81P	IPCTLZ600-81SP	1"-14	8	6.38			

OPTIONS:

- A - Anodized set screws
- SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
- K - Kit (Two insulated and one bare)
- R - Right hand design
- For omission of oxide inhibitor delete suffix "P"

Example:
IPCTLZ500-61SLP



Consult factory for additional configurations not listed