

Utility - Single Phase Transformer Connectors for Underground Use

PSMAL - Disconnectable "Screw-on" Transformer Connectors

- * Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- * Dual rated for copper or aluminum conductors
- * Range taking design reduces inventory
- * Rated for 600 Volts




PSMAL350-6SLP
SHOWN

Catalog Number	Stud Size	Number of Ports	Dimensions, Inches			Wire Range KCMIL
			L	W	H	
PSMAL350-4P	5/8"-11	4	5.69	2.26	1.25	350 - #10
PSMAL350-6P	5/8"-11	6	7.69			
PSMAL350-8P	5/8"-11	8	9.69			
PSMAL350-41P	1"-14	4	5.69	2.63	1.25	350 - #10
PSMAL350-61P	1"-14	6	7.69			
PSMAL350-81P	1"-14	8	9.69			
PSMAL500-458P	5/8"-11	4	6.25	2.50	1.63	500 - #10
PSMAL500-658P	5/8"-11	6	8.50			
PSMAL500-858P	5/8"-11	8	10.75			
PSMAL500-4P	1"-14	4	6.25	2.88	1.63	500 - #10
PSMAL500-6P	1"-14	6	8.50			
PSMAL500-8P	1"-14	8	10.75			
PSMAL-58P (Adapter Only)	5/8"-11	N/A	1.63	1.00	1.38	N/A
PSMAL-1P (Adapter Only)	1"-14	N/A	1.75	1.38	1.75	N/A

OPTIONS:

- CC - Slip on Cover (PTLEZCC Prefix)
 - A - Anodized set screws
 - T - Tin plated
 - SL - 1/0 - #14 Streetlight outlet, adds apx. 7/8" to length
 - K - Kit (Two insulated and one bare)
 - R - Right hand design
- For omission of oxide inhibitor delete suffix "P"



Consult factory for additional configurations not listed