

**Utility - Three Phase Transformer Connectors for Underground Use**

**PTLHK - Heavy Duty Transformer Lugs (Stacked Space Saving Connector)**

- \* Manufactured from high strength 6061-T6 aluminum alloy to provide premium electrical and mechanical performance
- \* Dual rated for copper or aluminum conductors
- \* Meets or exceeds ANSI C119.4 class A specifications
- \* Range taking design reduces inventory
- \* Rated for 600 volts
- \* Mounting holes at standard NEMA 1.75" spacing



PTLHK750-88P  
SHOWN

Catalog Number	Mounting Holes	Number of Ports	Dimensions, Inches			Wire Range KCMIL
			W	H	L	
PTLHK750-22P	2	2	1.44	4.00	8.63	750 - 1/0
PTLHK750-44P	4	4	2.75			
PTLHK750-66P	6	6	4.75			
PTLHK750-88P	8	8	6.50			
PTLHK750-1010P	10	10	8.00			
PTLHK750-1012P	10	12	8.00			
PTLHK750-1416P	14	16	11.50	4.00	8.63	1000 - 1/0
PTLHK1000-22P	2	2	1.75			
PTLHK1000-44P	4	4	3.25			
PTLHK1000-66P	6	6	4.75			
PTLHK1000-88P	8	8	6.50			
PTLHK1000-1010P	10	10	8.13			
PTLHK1000-1212P	12	12	9.75	4.00	8.63	1000 - 1/0
PTLHK1000-1416P	14	16	12.25			


**OPTIONS:**

A - Anodized set screws

T - Tin plated

For omission of oxide inhibitor delete suffix "P"

Covers available



Consult factory for additional configurations not listed